OM SENI

AO3406


30V N-Channel MOSFET

General Description

The AO3406 uses advanced trench technology to provide excellent $R_{DS(ON)}$ and low gate charge. This device is suitable for use as a load switch or in PWM applications.


Product Summary

V_{DS}	30V
I_D (at V_{GS}=10V)	3.6A
$R_{DS(ON)}$ (at V_{GS}=10V)	< 50mΩ
$R_{DS(ON)}$ (at V_{GS} =4.5V)	< 70mΩ



SOT-23

1 – Gate
2 – Source
3 – Drain



Absolute Maximum Ratings T_A=25℃ unless otherwise noted

Parameter		Symbol	Maximum	Units
Drain-Source Voltage		V_{DS}	30	V
Gate-Source Voltage		V_{GS}	±20	V
Continuous Drain Current	T_A=25℃	I_D	3.6	A
	T_A=70℃		2.9	
Pulsed Drain Current [C]		I_{DM}	15	
Power Dissipation [B]	T_A=25℃	P_D	1.4	W
	T_A=70℃		0.9	
Junction and Storage Temperature Range		T_J, T_{STG}	-55 to 150	℃

Thermal Characteristics

Parameter		Symbol	Typ	Max	Units
Maximum Junction-to-Ambient [A]	t ≤ 10s	$R_{\theta JA}$	70	90	℃/W
Maximum Junction-to-Ambient [A D]	Steady-State		100	125	℃/W
Maximum Junction-to-Lead	Steady-State	$R_{\theta JL}$	63	80	℃/W

OM SENI

Electrical Characteristics (T_J=25℃ unless otherwise noted)

Symbol	Parameter	Conditions	Min	Typ	Max	Units
STATIC PARAMETERS						
BV_{DSS}	Drain-Source Breakdown Voltage	I_D=250μA, V_{GS}=0V	30			V
I_{DSS}	Zero Gate Voltage Drain Current	V_{DS}=30V, V_{GS}=0V			1	μA
		T_J=55℃			5	
I_{GSS}	Gate-Body leakage current	V_{DS}=0V, V_{GS}= ±20V			±100	nA
$V_{GS(th)}$	Gate Threshold Voltage	V_{DS}=V_{GS} I_D=250μA	1.5	2	2.5	V
$I_{D(ON)}$	On state drain current	V_{GS}=10V, V_{DS}=5V	15			A
$R_{DS(ON)}$	Static Drain-Source On-Resistance	V_{GS}=10V, I_D=3.6A		36	50	mΩ
		T_J=125℃		57	80	
		V_{GS}=4.5V, I_D=2.8A		48	70	mΩ
g_{FS}	Forward Transconductance	V_{DS}=5V, I_D=3.6A		11		S
V_{SD}	Diode Forward Voltage	I_S=1A,V_{GS}=0V		0.79	1	V
I_S	Maximum Body-Diode Continuous Current				1.5	A
DYNAMIC PARAMETERS						
C_{iss}	Input Capacitance	V_{GS}=0V, V_{DS}=15V, f=1MHz		170	210	pF
C_{oss}	Output Capacitance			35		pF
C_{rss}	Reverse Transfer Capacitance			23		pF
R_g	Gate resistance	V_{GS}=0V, V_{DS}=0V, f=1MHz	1.7	3.5	5.3	Ω
SWITCHING PARAMETERS						
Q_g(10V)	Total Gate Charge	V_{GS}=10V, V_{DS}=15V, I_D=3.6A		4.05	5	nC
Q_g(4.5V)	Total Gate Charge			2	3	nC
Q_{gs}	Gate Source Charge			0.55		nC
Q_{gd}	Gate Drain Charge			1		nC
$t_{D(on)}$	Turn-On DelayTime	V_{GS}=10V, V_{DS}=15V, R_L=2.2Ω, R_{GEN}=3Ω		4.5		ns
t_r	Turn-On Rise Time			1.5		ns
$t_{D(off)}$	Turn-Off DelayTime			18.5		ns
t_f	Turn-Off Fall Time			15.5		ns
t_{rr}	Body Diode Reverse Recovery Time	I_F=3.6A, dI/dt=100A/μs		7.5	10	ns
Q_{rr}	Body Diode Reverse Recovery Charge	I_F=3.6A, dI/dt=100A/μs		2.5		nC

OM SENI

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




Fig 1: On-Region Characteristics (Note E)




Figure 2: Transfer Characteristics (Note E)




Figure 3: On-Resistance vs. Drain Current and Gate Voltage (Note E)




Figure 4: On-Resistance vs. Junction Temperature (Note E)




Figure 5: On-Resistance vs. Gate-Source Voltage (Note E)




Figure 6: Body-Diode Characteristics (Note E)

OM SENI

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




Figure 7: Gate-Charge Characteristics




Figure 8: Capacitance Characteristics




Figure 9: Maximum Forward Biased Safe Operating Area (Note F)




Figure 10: Single Pulse Power Rating Junction-to-Ambient (Note F)





Figure 11: Normalized Maximum Transient Thermal Impedance (Note F)

OM SENI

Ordering Information


PACKAGE	PACKAGE CODE	UNIT WEIGHT(g)	REEL(pcs)	BOX(pcs)	CARTON(pcs)	DELIVERY MODE
SOT-23	R1	0.008	3000	30000	240000	7''

Package Outline Dimensions (SOT-23)



Symbol	Dimensions			
	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A	0.90	1.15	0.035	0.045
A1	-	0.10	-	0.004
A2	0.90	1.05	0.035	0.041
b	0.30	0.50	0.012	0.020
c	0.10	0.20	0.004	0.008
D	2.80	3.00	0.110	0.118
E	1.20	1.40	0.047	0.055
E1	2.25	2.55	0.089	0.100
e	0.950TYP		0.037TYP	
e1	1.80	2.00	0.071	0.079
L	0.550REF		0.022REF	
L1	0.30	0.50	0.012	0.020
θ	-	8°	-	8°

Suggested Pad Layout



Symbol	Dimensions			
	Millimeters		Inches	
	Min.	Max.	Min.	Max.
J	0.75	0.85	0.030	0.033
K	0.85	0.95	0.033	0.037
M	1.95	2.05	0.077	0.081
N	1.85	1.95	0.073	0.077