OM SENI

# AO4262E

## 60V N-Channel AlphaSGT™

### General Description

- Trench Power AlphaSGT™ technology
- Low $R_{DS(ON)}$
- Low Gate Charge
- ESD protected


### Applications


- High efficiency power supply
- Secondary synchronus rectifier

### Product Summary

| | |
|---|---|
| $V_{DS}$ | 60V |
| $I_D$ (at $V_{GS}$=10V) | 16.5A |
| $R_{DS(ON)}$ (at $V_{GS}$=10V) | < 6.5mΩ |
| $R_{DS(ON)}$ (at $V_{GS}$=4.5V) | < 8.5mΩ |
| **Typical ESD protection** | **HBM Class 2** |

100% UIS Tested
100% Rg Tested




| Orderable Part Number | Package Type | Form | Minimum Order Quantity |
|---|---|---|---|
| AO4262E | SO-8 | Tape & Reel | 3000 |

**Absolute Maximum Ratings $T_A$=25°C unless otherwise noted**

| Parameter | | Symbol | Maximum | Units |
|---|---|---|---|---|
| Drain-Source Voltage | | $V_{DS}$ | 60 | V |
| Gate-Source Voltage | | $V_{GS}$ | ±20 | V |
| Continuous Drain Current | $T_A$=25°C | $I_D$ | 16.5 | A |
| | $T_A$=70°C | | 13.0 | |
| Pulsed Drain Current [C] | | $I_{DM}$ | 65 | |
| Avalanche Current [C] | | $I_{AS}$ | 23 | A |
| Avalanche energy | L=0.3mH [C] | $E_{AS}$ | 79 | mJ |
| $V_{DS}$ Spike [G] | 10µs | $V_{SPIKE}$ | 72 | V |
| Power Dissipation [B] | $T_A$=25°C | $P_D$ | 3.1 | W |
| | $T_A$=70°C | | 2.0 | |
| Junction and Storage Temperature Range | | $T_J$, $T_{STG}$ | -55 to 150 | °C |

**Thermal Characteristics**

| Parameter | | Symbol | Typ | Max | Units |
|---|---|---|---|---|---|
| Maximum Junction-to-Ambient [A] | t ≤ 10s | $R_{\theta JA}$ | 31 | 40 | °C/W |
| Maximum Junction-to-Ambient [A D] | Steady-State | | 59 | 75 | °C/W |
| Maximum Junction-to-Lead | Steady-State | $R_{\theta JL}$ | 16 | 24 | °C/W |

OM SENI

**Electrical Characteristics ($T_J$=25°C unless otherwise noted)**

| Symbol | Parameter | Conditions | Min | Typ | Max | Units |
|---|---|---|---|---|---|---|
| **STATIC PARAMETERS** | | | | | | |
| $BV_{DSS}$ | Drain-Source Breakdown Voltage | $I_D$=250µA, $V_{GS}$=0V | 60 | | | V |
| $I_{DSS}$ | Zero Gate Voltage Drain Current | $V_{DS}$=60V, $V_{GS}$=0V | | | 1 | µA |
| | | $T_J$=55°C | | | 5 | |
| $I_{GSS}$ | Gate-Body leakage current | $V_{DS}$=0V, $V_{GS}$=±20V | | | ±10 | µA |
| $V_{GS(th)}$ | Gate Threshold Voltage | $V_{DS}$=$V_{GS}$, $I_D$=250µA | 1.2 | 1.65 | 2.2 | V |
| $R_{DS(ON)}$ | Static Drain-Source On-Resistance | $V_{GS}$=10V, $I_D$=16.5A | | 5.2 | 6.5 | mΩ |
| | | $T_J$=125°C | | 8.3 | 10.5 | |
| | | $V_{GS}$=4.5V, $I_D$=14.5A | | 6.6 | 8.5 | mΩ |
| $g_{FS}$ | Forward Transconductance | $V_{DS}$=5V, $I_D$=16.5A | | 70 | | S |
| $V_{SD}$ | Diode Forward Voltage | $I_S$=1A, $V_{GS}$=0V | | 0.7 | 1 | V |
| $I_S$ | Maximum Body-Diode Continuous Current | | | | 4 | A |
| **DYNAMIC PARAMETERS** | | | | | | |
| $C_{iss}$ | Input Capacitance | $V_{GS}$=0V, $V_{DS}$=30V, f=1MHz | | 1652 | | pF |
| $C_{oss}$ | Output Capacitance | | | 520 | | pF |
| $C_{rss}$ | Reverse Transfer Capacitance | | | 52 | | pF |
| $R_g$ | Gate resistance | f=1MHz | 0.6 | 1.3 | 2.0 | Ω |
| **SWITCHING PARAMETERS** | | | | | | |
| $Q_g$(10V) | Total Gate Charge | $V_{GS}$=10V, $V_{DS}$=30V, $I_D$=16.5A | | 30 | 45 | nC |
| $Q_g$(4.5V) | Total Gate Charge | | | 15 | 25 | nC |
| $Q_{gs}$ | Gate Source Charge | | | 3.5 | | nC |
| $Q_{gd}$ | Gate Drain Charge | | | 6.5 | | nC |
| $t_{D(on)}$ | Turn-On DelayTime | $V_{GS}$=10V, $V_{DS}$=30V, $R_L$=1.8Ω, $R_{GEN}$=3Ω | | 6 | | ns |
| $t_r$ | Turn-On Rise Time | | | 5 | | ns |
| $t_{D(off)}$ | Turn-Off DelayTime | | | 29 | | ns |
| $t_f$ | Turn-Off Fall Time | | | 7 | | ns |
| $t_{rr}$ | Body Diode Reverse Recovery Time | $I_F$=16.5A, di/dt=500A/µs | | 19 | | ns |
| $Q_{rr}$ | Body Diode Reverse Recovery Charge | $I_F$=16.5A, di/dt=500A/µs | | 60 | | nC |

A. The value of $R_{\theta JA}$ is measured with the device mounted on 1in² FR-4 board with 2oz. Copper, in a still air environment with $T_A$ =25° C. The value in any given application depends on the user's specific board design.
B. The power dissipation $P_D$ is based on $T_{J(MAX)}$=150° C, using ≤ 10s junction-to-ambient thermal resistance.
C. Repetitive rating, pulse width limited by junction temperature $T_{J(MAX)}$=150° C. Ratings are based on low frequency and duty cycles to keep initial$T_J$=25° C.
D. The $R_{\theta JA}$ is the sum of the thermal impedance from junction to lead $R_{\theta JL}$ and lead to ambient.
E. The static characteristics in Figures 1 to 6 are obtained using <300µs pulses, duty cycle 0.5% max.
F. These curves are based on the junction-to-ambient thermal impedance which is measured with the device mounted on 1in² FR-4 board with 2oz. Copper, assuming a maximum junction temperature of $T_{J(MAX)}$=150° C. The SOA curve provides a single pulse rating.
G. The spike duty cycle 5% max, limited by junction temperature TJ(MAX)=125° C.

OM SENI

## TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS





Figure 1: On-Region Characteristics (Note E)





Figure 2: Transfer Characteristics (Note E)





Figure 3: On-Resistance vs. Drain Current and Gate Voltage (Note E)





Figure 4: On-Resistance vs. Junction Temperature (Note E)





Figure 5: On-Resistance vs. Gate-Source Voltage (Note E)





Figure 6: Body-Diode Characteristics (Note E)

OM SENI

## TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS





Figure 7: Gate-Charge Characteristics





Figure 8: Capacitance Characteristics





Figure 9: Maximum Forward Biased Safe Operating Area (Note F)





Figure 10: Single Pulse Power Rating Junction-to-Ambient (Note F)







Figure 11: Normalized Maximum Transient Thermal Impedance (Note F)

# OM SENI


Gate Charge Test Circuit & Waveform




Resistive Switching Test Circuit & Waveforms




Unclamped Inductive Switching (UIS) Test Circuit & Waveforms




Diode Recovery Test Circuit & Waveforms

