OM SENI

AO4406A

30V N-Channel MOSFET


General Description


The AO4406A uses advanced trench technology to provide excellent $R_{DS(ON)}$ with low gate charge.
This device is suitable for high side switch in SMPS and general purpose applications.

Product Summary

V_{DS}	30V
I_D (at V_{GS}=10V)	13A
$R_{DS(ON)}$ (at V_{GS}=10V)	< 11.5mΩ
$R_{DS(ON)}$ (at V_{GS} = 4.5V)	< 15.5mΩ

100% UIS Tested
100% R_g Tested





Orderable Part Number	Package Type	Form	Minimum Order Quantity
	SO-8	Tape & Reel	3000

Absolute Maximum Ratings T_A=25℃ unless otherwise noted

Parameter		Symbol	Maximum	Units
Drain-Source Voltage		V_{DS}	30	V
Gate-Source Voltage		V_{GS}	±20	V
Continuous Drain Current	T_A=25℃	I_D	13	A
	T_A=70℃		10.4	
Pulsed Drain Current [C]		I_{DM}	100	
Avalanche Current [C]		I_{AS}	22	A
Avalanche energy L=0.1mH [C]		E_{AS}	24	mJ
Power Dissipation [B]	T_A=25℃	P_D	3.1	W
	T_A=70℃		2	
Junction and Storage Temperature Range		T_J, T_{STG}	-55 to 150	℃

Thermal Characteristics

Parameter		Symbol	Typ	Max	Units
Maximum Junction-to-Ambient [A]	t ≤ 10s	$R_{\theta JA}$	31	40	℃/W
Maximum Junction-to-Ambient [A D]	Steady-State		59	75	℃/W
Maximum Junction-to-Lead	Steady-State	$R_{\theta JL}$	16	24	℃/W

OM SENI

Electrical Characteristics (T_J=25℃ unless otherwise noted)

Symbol	Parameter	Conditions	Min	Typ	Max	Units
STATIC PARAMETERS						
BV_{DSS}	Drain-Source Breakdown Voltage	I_D=250μA, V_{GS}=0V	30			V
I_{DSS}	Zero Gate Voltage Drain Current	V_{DS}=30V, V_{GS}=0V			1	μA
		T_J=55℃			5	
I_{GSS}	Gate-Body leakage current	V_{DS}=0V, V_{GS}=±20V			±100	nA
$V_{GS(th)}$	Gate Threshold Voltage	V_{DS}=V_{GS} I_D=250μA	1.5	1.9	2.5	V
$I_{D(ON)}$	On state drain current	V_{GS}=10V, V_{DS}=5V	100			A
$R_{DS(ON)}$	Static Drain-Source On-Resistance	V_{GS}=10V, I_D=12A		9.5	11.5	mΩ
		T_J=125℃		14	17	
		V_{GS}=4.5V, I_D=10A		12.5	15.5	mΩ
g_{FS}	Forward Transconductance	V_{DS}=5V, I_D=12A		45		S
V_{SD}	Diode Forward Voltage	I_S=1A,V_{GS}=0V		0.75	1	V
I_S	Maximum Body-Diode Continuous Current				4	A
DYNAMIC PARAMETERS						
C_{iss}	Input Capacitance	V_{GS}=0V, V_{DS}=15V, f=1MHz	610	760	910	pF
C_{oss}	Output Capacitance		88	125	160	pF
C_{rss}	Reverse Transfer Capacitance		40	70	100	pF
R_g	Gate resistance	V_{GS}=0V, V_{DS}=0V, f=1MHz	0.8	1.6	2.4	Ω
SWITCHING PARAMETERS						
Q_g(10V)	Total Gate Charge	V_{GS}=10V, V_{DS}=15V, I_D=12A	11	14	17	nC
Q_g(4.5V)	Total Gate Charge		5	6.6	8	nC
Q_{gs}	Gate Source Charge		1.9	2.4	2.9	nC
Q_{gd}	Gate Drain Charge		1.8	3	4.2	nC
Q_{gs}	Gate Source Charge	V_{GS}=4.5V, V_{DS}=15V, I_D=12A	1.9	2.4	2.9	nC
Q_{gd}	Gate Drain Charge		1.8	3	4.2	nC
$t_{D(on)}$	Turn-On DelayTime	V_{GS}=10V, V_{DS}=15V, R_L=1.25Ω, R_{GEN}=3Ω		4.4		ns
t_r	Turn-On Rise Time			9		ns
$t_{D(off)}$	Turn-Off DelayTime			17		ns
t_f	Turn-Off Fall Time			6		ns
t_{rr}	Body Diode Reverse Recovery Time	I_F=12A, dI/dt=500A/μs	5.6	7	8	ns
Q_{rr}	Body Diode Reverse Recovery Charge	I_F=12A, dI/dt=500A/μs	6.4	8	9.6	nC

A. The value of $R_{\theta JA}$ is measured with the device mounted on 1in² FR-4 board with 2oz. Copper, in a still air environment with T_A =25° C. The value in any given application depends on the user's specific board design.
B. The power dissipation P_D is based on $T_{J(MAX)}$=150° C, using ≤ 10s junction-to-ambient thermal resistance.
C. Repetitive rating, pulse width limited by junction temperature $T_{J(MAX)}$=150° C. Ratings are based on low frequency and duty cycles to keep initialT_J=25° C.
D. The $R_{\theta JA}$ is the sum of the thermal impedence from junction to lead $R_{\theta JL}$ and lead to ambient.
E. The static characteristics in Figures 1 to 6 are obtained using <300μs pulses, duty cycle 0.5% max.
F. These curves are based on the junction-to-ambient thermal impedence which is measured with the device mounted on 1in² FR-4 board with 2oz. Copper, assuming a maximum junction temperature of $T_{J(MAX)}$=150° C. The SOA curve provides a single pulse rating.

OM SENI

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




Fig 1: On-Region Characteristics (Note E)






Figure 2: Transfer Characteristics (Note E)








Figure 5: On-Resistance vs. Gate-Source Voltage (Note E)




Figure 6: Body-Diode Characteristics (Note E)

OM SENI

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




Figure 7: Gate-Charge Characteristics






Figure 8: Capacitance Characteristics





Safe Operating Area (Note F)




Figure 11: Single Pulse Power Rating Junction-to-Ambient (Note F)

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS






Figure 12: Normalized Maximum Transient Thermal Impedance (Note F)

OM SENI


Gate Charge Test Circuit & Waveform



Resistive Switching Test Circuit & Waveforms



Unclamped Inductive Switching (UIS) Test Circuit & Waveforms



Diode Recovery Test Circuit & Waveforms

