OM SENI

AO4441


60V P-Channel MOSFET

General Description

The AO4441 uses advanced trench technology to provide excellent $R_{DS(ON)}$, and ultra-low low gate charge. This device is suitable for use as a load switch or in PWM applications.

Product Summary

V_{DS}	-60V
I_D (at V_{GS}=-10V)	-4A
$R_{DS(ON)}$ (at V_{GS}=-10V)	< 100mΩ
$R_{DS(ON)}$ (at V_{GS} = -4.5V)	< 130mΩ



Orderable Part Number	Package Type	Form	Minimum Order Quantity
	SO-8	Tape & Reel	3000

Absolute Maximum Ratings T_A=25℃ unless otherwise noted

Parameter		Symbol	Maximum	Units
Drain-Source Voltage		V_{DS}	-60	V
Gate-Source Voltage		V_{GS}	±20	V
Continuous Drain Current [A]	T_A=25℃	I_D	-4	A
	T_A=70℃		-3.1	
Pulsed Drain Current [B]		I_{DM}	-20	
Power Dissipation [A]	T_A=25℃	P_D	3.1	W
	T_A=70℃		2	
Junction and Storage Temperature Range		T_J, T_{STG}	-55 to 150	℃

Thermal Characteristics					
Parameter		**Symbol**	**Typ**	**Max**	**Units**
Maximum Junction-to-Ambient [A]	t ≤ 10s	$R_{\theta JA}$	24	40	℃/W
Maximum Junction-to-Ambient [A]	Steady-State		54	75	℃/W
Maximum Junction-to-Lead [C]	Steady-State	$R_{\theta JL}$	21	30	℃/W

OM SENI

Electrical Characteristics (T_J=25℃ unless otherwise noted)

Symbol	Parameter	Conditions	Min	Typ	Max	Units
STATIC PARAMETERS						
BV_{DSS}	Drain-Source Breakdown Voltage	I_D=-250μA, V_{GS}=0V	-60			V
I_{DSS}	Zero Gate Voltage Drain Current	V_{DS}=-48V, V_{GS}=0V			-1	μA
		T_J=55℃			-5	
I_{GSS}	Gate-Body leakage current	V_{DS}=0V, V_{GS}= ±20V			±100	nA
$V_{GS(th)}$	Gate Threshold Voltage	V_{DS}=V_{GS}, I_D=-250μA	-1	-2.1	-3	V
$R_{DS(ON)}$	Static Drain-Source On-Resistance	V_{GS}=-10V, I_D=-4A		80	100	mΩ
		T_J=125℃		130		
		V_{GS}=-4.5V, I_D=-3A		102	130	mΩ
g_{FS}	Forward Transconductance	V_{DS}=-5V, I_D=-4A		10		S
V_{SD}	Diode Forward Voltage	I_S=-1A,V_{GS}=0V		-0.77	-1	V
I_S	Maximum Body-Diode Continuous Current				-4	A
DYNAMIC PARAMETERS						
C_{iss}	Input Capacitance	V_{GS}=0V, V_{DS}=-30V, f=1MHz		930	1120	pF
C_{oss}	Output Capacitance			85		pF
C_{rss}	Reverse Transfer Capacitance			35		pF
R_g	Gate resistance	f=1MHz		7.2	9	Ω
SWITCHING PARAMETERS						
Q_g(10V)	Total Gate Charge	V_{GS}=-10V, V_{DS}=-30V, I_D=-4A		16	20	nC
Q_g(4.5V)	Total Gate Charge			8	10	nC
Q_{gs}	Gate Source Charge			2.5		nC
Q_{gd}	Gate Drain Charge			3.2		nC
$t_{D(on)}$	Turn-On DelayTime	V_{GS}=-10V, V_{DS}=-30V, R_L=7.5Ω, R_{GEN}=3Ω		8		ns
t_r	Turn-On Rise Time			3.8		ns
$t_{D(off)}$	Turn-Off DelayTime			31.5		ns
t_f	Turn-Off Fall Time			7.5		ns
t_{rr}	Body Diode Reverse Recovery Time	I_F=-4A, dI/dt=100A/μs		27	35	ns
Q_{rr}	Body Diode Reverse Recovery Charge	I_F=-4A, dI/dt=100A/μs		32		nC

A: The value of $R_{\theta JA}$ is measured with the device mounted on 1in^2 FR-4 board with 2oz. Copper, in a still air environment with T_A=25° C. The value in any a given application depends on the user's specific board design. The current rating is based on the t ≤ 10s thermal resistance rating.
B: Repetitive rating, pulse width limited by junction temperature.
C. The $R_{\theta JA}$ is the sum of the thermal impedence from junction to lead $R_{\theta JL}$ and lead to ambient.
D. The static characteristics in Figures 1 to 6,12,14 are obtained using 80 μs pulses, duty cycle 0.5% max.
E. These tests are performed with the device mounted on 1 in ^{2} FR-4 board with 2oz. Copper, in a still air environment with T_A=25° C. The SOA curve provides a single pulse rating.

OM SENI

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




Fig 1: On-Region Characteristics




Figure 2: Transfer Characteristics




Figure 3: On-Resistance vs. Drain Current and Gate Voltage




Figure 4: On-Resistance vs. Junction Temperature




Figure 5: On-Resistance vs. Gate-Source Voltage




Figure 6: Body-Diode Characteristics

OM SENI

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




Figure 7: Gate-Charge Characteristics




Figure 8: Capacitance Characteristics




Figure 9: Maximum Forward Biased Safe Operating Area (Note E)




Figure 10: Single Pulse Power Rating Junction-to-Ambient (Note E)






Figure 11: Normalized Maximum Transient Thermal Impedance

OM SENI


Gate Charge Test Circuit & Waveform



Resistive Switching Test Circuit & Waveforms



Unclamped Inductive Switching (UIS) Test Circuit & Waveforms



Diode Recovery Test Circuit & Waveforms

