OM SENI

AOD7S65

650V 7A αMOS™ Power Transistor


General Description


The AOD7S65 have been fabricated using the advanced αMOS™ high voltage process that is designed to deliver high levels of performance and robustness in switching applications. By providing low $R_{DS(on)}$, Q_g and E_{OSS} along with guaranteed avalanche capability these parts can be adopted quickly into new and existing offline power supply designs.

Product Summary

V_{DS} @ $T_{j,max}$	750V
I_{DM}	30A
$R_{DS(ON),max}$	0.65Ω
$Q_{g,typ}$	9.2nC
E_{oss} @ 400V	2μJ

100% UIS Tested
100% R_g Tested





Orderable Part Number	Package Type	Form	Minimum Order Quantity
	TO-252	Tape & Reel	2500

Absolute Maximum Ratings T_A=25℃ unless otherwise noted

Parameter		Symbol	Maximum	Units
Drain-Source Voltage		V_{DS}	650	V
Gate-Source Voltage		V_{GS}	±30	V
Continuous Drain Current	T_C=25℃	I_D	7	A
	T_C=100℃		5	
Pulsed Drain Current [C]		I_{DM}	30	
Avalanche Current [C]		I_{AR}	1.7	A
Repetitive avalanche energy [C]		E_{AR}	43	mJ
Single pulsed avalanche energy [H]		E_{AS}	86	mJ
Power Dissipation [B]	T_C=25℃	P_D	89	W
	Derate above 25°C		0.7	W/ °C
MOSFET dv/dt ruggedness		dv/dt	100	V/ns
Peak diode recovery dv/dt			20	
Junction and Storage Temperature Range		T_J, T_{STG}	-55 to 150	℃
Maximum lead temperature for soldering purpose, 1/8" from case for 5 seconds [K]		T_L	300	℃

Thermal Characteristics

Parameter	Symbol	Typical	Maximum	Units
Maximum Junction-to-Ambient [A,D]	$R_{\theta JA}$	45	55	℃/W
Maximum Case-to-sink [A]	$R_{\theta CS}$	--	0.5	℃/W
Maximum Junction-to-Case [D,F]	$R_{\theta JC}$	1.1	1.4	℃/W

OM SENI

Electrical Characteristics (T_J=25℃ unless otherwise noted)

Symbol	Parameter	Conditions	Min	Typ	Max	Units
STATIC PARAMETERS						
BV_{DSS}	Drain-Source Breakdown Voltage	I_D=250μA, V_{GS}=0V, T_J=25℃	650	-	-	V
		I_D=250μA, V_{GS}=0V, T_J=150℃	700	750	-	
I_{DSS}	Zero Gate Voltage Drain Current	V_{DS}=650V, V_{GS}=0V	-	-	1	μA
		V_{DS}=520V, T_J=150℃	-	10	-	
I_{GSS}	Gate-Body leakage current	V_{DS}=0V, V_{GS}=±30V	-	-	±100	nA
$V_{GS(th)}$	Gate Threshold Voltage	V_{DS}=5V,I_D=250μA	2.6	3.3	4	V
$R_{DS(ON)}$	Static Drain-Source On-Resistance	V_{GS}=10V, I_D=3.5A, T_J=25℃	-	0.54	0.65	Ω
		V_{GS}=10V, I_D=3.5A, T_J=150℃	-	1.48	1.64	Ω
V_{SD}	Diode Forward Voltage	I_S=3.5A,V_{GS}=0V, T_J=25℃	-	0.82	-	V
I_S	Maximum Body-Diode Continuous Current		-	-	7	A
I_{SM}	Maximum Body-Diode Pulsed Current[C]		-	-	30	A
DYNAMIC PARAMETERS						
C_{iss}	Input Capacitance	V_{GS}=0V, V_{DS}=100V, f=1MHz	-	434	-	pF
C_{oss}	Output Capacitance		-	30	-	pF
$C_{o(er)}$	Effective output capacitance, energy related[I]	VGS=0V, V_{DS}=0 to 480V, f=1MHz	-	23	-	pF
$C_{o(tr)}$	Effective output capacitance, time related[J]		-	80	-	pF
C_{rss}	Reverse Transfer Capacitance	VGS=0V, V_{DS}=100V, f=1MHz	-	1	-	pF
R_g	Gate resistance	V_{GS}=0V, V_{DS}=0V, f=1MHz	-	17.5	-	Ω
SWITCHING PARAMETERS						
Q_g	Total Gate Charge	V_{GS}=10V, V_{DS}=480V, I_D=3.5A	-	9.2	-	nC
Q_{gs}	Gate Source Charge		-	2.5	-	nC
Q_{gd}	Gate Drain Charge		-	2.7	-	nC
$t_{D(on)}$	Turn-On DelayTime	V_{GS}=10V, V_{DS}=400V, I_D=3.5A, R_G=25Ω	-	21	-	ns
t_r	Turn-On Rise Time		-	14	-	ns
$t_{D(off)}$	Turn-Off DelayTime		-	55	-	ns
t_f	Turn-Off Fall Time		-	15	-	ns
t_{rr}	Body Diode Reverse Recovery Time	I_F=3.5A,dI/dt=100A/μs,V_{DS}=400V	-	224	-	ns
I_{rm}	Peak Reverse Recovery Current	I_F=3.5A,dI/dt=100A/μs,V_{DS}=400V	-	19	-	A
Q_{rr}	Body Diode Reverse Recovery Charge	I_F=3.5A,dI/dt=100A/μs,V_{DS}=400V	-	2.8	-	μC

A. The value of $R_{\theta JA}$ is measured with the device in a still air environment with T_A=25℃.

B. The power dissipation P_D is based on $T_{J(MAX)}$=150℃, using junction-to-case thermal resistance, and is more useful in setting the upper dissipation limit for cases where additional heatsinking is used.

C. Repetitive rating, pulse width limited by junction temperature $T_{J(MAX)}$=150℃, Ratings are based on low frequency and duty cycles to keep initial T_J =25℃.

D. The $R_{\theta JA}$ is the sum of the thermal impedance from junction to case $R_{\theta JC}$ and case to ambient.

E. The static characteristics in Figures 1 to 6 are obtained using <300 μs pulses, duty cycle 0.5% max.

F. These curves are based on the junction-to-case thermal impedance which is measured with the device mounted to a large heatsink, assuming a maximum junction temperature of $T_{J(MAX)}$=150℃. The SOA curve provides a single pulse ratin g.

G. These tests are performed with the device mounted on 1 in^2 FR-4 board with 2oz. Copper, in a still air environment with T_A=25℃.

H. L=60mH, I_{AS}=1.7A, V_{DD}=150V, Starting T_J=25℃

I. $C_{o(er)}$ is a fixed capacitance that gives the same stored energy as C_{oss} while V_{DS} is rising from 0 to 80% $V_{(BR)DSS}$.

J. $C_{o(tr)}$ is a fixed capacitance that gives the same charging time as C_{oss} while V_{DS} is rising from 0 to 80% $V_{(BR)DSS}$.

K. Wave soldering only allowed at leads.

OM SENI

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




Figure 1: On-Region Characteristics@25℃




Figure 2: On-Region Characteristics@125℃




Figure 3: Transfer Characteristics




Figure 4: On-Resistance vs. Drain Current and Gate Voltage




Figure 5: On-Resistance vs. Junction Temperature




Figure 6: Break Down vs. Junction Temperature

OM SENI

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




Figure 7: Body-Diode Characteristics (Note E)




Figure 8: Gate-Charge Characteristics




Figure 9: Capacitance Characteristics




Figure 10: Coss stored Energy




Figure 11: Maximum Forward Biased Safe Operating Area (Note F)




Figure 12: Single Pulse Power Rating Junction-to-Case (Note F)

OM SENI

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




Figure 13: Normalized Maximum Transient Thermal Impedance (Note F)




Figure 14: Avalanche energy




Figure 15: Current De-rating (Note B)

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




Figure 16: Single Pulse Power Rating Junction-to-Ambient (Note G)






Figure 17: Normalized Maximum Transient Thermal Impedance (Note G)

OM SENI


Gate Charge Test Circuit & Waveform



Resistive Switching Test Circuit & Waveforms



Unclamped Inductive Switching (UIS) Test Circuit & Waveforms



Diode Recovery Test Circuit & Waveforms

