www.omseni.com

OM SENI

Si2323CDS-T1-GE3
P-Channel 20 V (D-S) MOSFET


MOSFET PRODUCT SUMMARY			
V_{DS} (V)	$R_{DS(on)}$ (Ω)	I_D (A)[a]	Q_g (Typ.)
-20	0.039 at V_{GS} = -4.5 V	-6[e]	9 nC
	0.050 at V_{GS} = -2.5 V	-5.8	
	0.063 at V_{GS} = -1.8 V	-5.1	

FEATURES

- TrenchFET® Power MOSFET
- 100 % R_g Tested
- Material categorization:


APPLICATIONS

- Load Switch
- PA Switch
- DC/DC Converters



SOT–23

1 – Gate
2 – Source
3 – Drain



Ordering Information:
Si2323CDS-T1-GE3 (Lead (Pb)-free and Halogen-free)

ABSOLUTE MAXIMUM RATINGS (T_A = 25 °C, unless otherwise noted)				
Parameter		**Symbol**	**Limit**	**Unit**
Drain-Source Voltage		V_{DS}	-20	V
Gate-Source Voltage		V_{GS}	± 8	
Continuous Drain Current (T_J = 150 °C)	T_C = 25 °C	I_D	-6[e]	A
	T_C = 70 °C		-5.2	
	T_A = 25 °C		-4.6[b, c]	
	T_A = 70 °C		-3.7[b, c]	
Pulsed Drain Current		I_{DM}	-20	
Continuous Source-Drain Diode Current	T_C = 25 °C	I_S	-2.1	
	T_A = 25 °C		-1[b, c]	
Maximum Power Dissipation	T_C = 25 °C	P_D	2.5	W
	T_C = 70 °C		1.6	
	T_A = 25 °C		1.25[b, c]	
	T_A = 70 °C		0.8[b, c]	
Operating Junction and Storage Temperature Range		T_J, T_{stg}	-55 to 150	°C

THERMAL RESISTANCE RATINGS					
Parameter		**Symbol**	**Typical**	**Maximum**	**Unit**
Maximum Junction-to-Ambient[b, d]	≤ 5 s	R_{thJA}	75	100	°C/W
Maximum Junction-to-Foot (Drain)	Steady State	R_{thJF}	40	50	


OM SENI

MOSFET SPECIFICATIONS (T_J = 25 °C, unless otherwise noted)						
Parameter	**Symbol**	**Test Conditions**	**Min.**	**Typ.**	**Max.**	**Unit**
Static						
Drain-Source Breakdown Voltage	V_{DS}	V_{DS} = 0 V, I_D = -250 µA	-20			V
V_{DS} Temperature Coefficient	$\Delta V_{DS}/T_J$	I_D = -250 µA		-14		mV/°C
$V_{GS(th)}$ Temperature Coefficient	$\Delta V_{GS(th)}/T_J$			2.4		
Gate-Source Threshold Voltage	$V_{GS(th)}$	V_{DS} = V_{GS}, I_D = -250 µA	-0.4		-1	V
Gate-Source Leakage	I_{GSS}	V_{DS} = 0 V, V_{GS} = ± 8 V			± 100	nA
Zero Gate Voltage Drain Current	I_{DSS}	V_{DS} = -20 V, V_{GS} = 0 V			-1	µA
		V_{DS} = -20 V, V_{GS} = 0 V, T_J = 55 °C			-10	
On-State Drain Current[a]	$I_{D(on)}$	V_{DS} ≤ -5 V, V_{GS} = -4.5 V	-20			A
Drain-Source On-State Resistance[a]	$R_{DS(on)}$	V_{GS} = -4.5 V, I_D = -4.6 A		0.032	0.039	Ω
		V_{GS} = -2.5 V, I_D = -4.1 A		0.041	0.050	
		V_{GS} = -1.8 V, I_D = -3.6 A		0.050	0.063	
Forward Transconductance[a]	g_{fs}	V_{DS} = -5 V, I_D = -4.6 A		20		S
Dynamic[b]						
Input Capacitance	C_{iss}	V_{DS} = -10 V, V_{GS} = 0 V, f = 1 MHz		1090		pF
Output Capacitance	C_{oss}			155		
Reverse Transfer Capacitance	C_{rss}			135		
Total Gate Charge	Q_g	V_{DS} = -10 V, V_{GS} = -4.5 V, I_D = -4.6 A		16	25	nC
		V_{DS} = -10 V, V_{GS} = -2.5 V, I_D = -4.6 A		9.3	15	
Gate-Source Charge	Q_{gs}			2.5		
Gate-Drain Charge	Q_{gd}			3.2		
Gate Resistance	R_g	f = 1 MHz	0.8	4.1	8.2	Ω
Turn-On Delay Time	$t_{d(on)}$	V_{DD} = -10 V, R_L = 2.7 Ω I_D = -3.7 A, V_{GEN} = -4.5 V, R_g = 1 Ω		15	23	ns
Rise Time	t_r			23	35	
Turn-Off Delay Time	$t_{d(off)}$			40	60	
Fall Time	t_f			12	20	
Drain-Source Body Diode Characteristics						
Continuous Source-Drain Diode Current	I_S	T_C = 25 °C			-2.1	A
Pulse Diode Forward Current[a]	I_{SM}				-20	
Body Diode Voltage	V_{SD}	I_S = -3.7 A		-0.8	-1.2	V
Body Diode Reverse Recovery Time	t_{rr}	I_F = -3.7 A, dI/dt = 100 A/µs, T_J = 25 °C		30	45	ns
Body Diode Reverse Recovery Charge	Q_{rr}			20	40	nC
Reverse Recovery Fall Time	t_a			17		ns
Reverse Recovery Rise Time	t_b			13		


Notes:
a. Pulse test; pulse width ≤ 300 µs, duty cycle ≤ 2 %.
b. Guaranteed by design, not subject to production testing.

OM SENI


TYPICAL CHARACTERISTICS (25 °C, unless otherwise noted)




Output Characteristics




Transfer Characteristics




On-Resistance vs. Drain Current and Gate Voltage



Capacitance




Gate Charge




On-Resistance vs. Junction Temperature

OM SENI


TYPICAL CHARACTERISTICS (25 °C, unless otherwise noted)




Source-Drain Diode Forward Voltage




On-Resistance vs. Gate-to-Source Voltage



Threshold Voltage




Single Pulse Power




Safe Operating Area

OM SENI


TYPICAL CHARACTERISTICS (25 °C, unless otherwise noted)



Current Derating*




Power, Junction-to-Foot




Power, Junction-to-Ambient

TYPICAL CHARACTERISTICS (25 °C, unless otherwise noted)



Normalized Thermal Transient Impedance, Junction-to-Ambient




Normalized Thermal Transient Impedance, Junction-to-Foot

OM SENI

Ordering Information


PACKAGE	PACKAGE CODE	UNIT WEIGHT(g)	REEL(pcs)	BOX(pcs)	CARTON(pcs)	DELIVERY MODE
SOT-23	R1	0.008	3000	30000	240000	7''

Package Outline Dimensions (SOT-23)



Symbol	Dimensions			
	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A	0.90	1.15	0.035	0.045
A1	-	0.10	-	0.004
A2	0.90	1.05	0.035	0.041
b	0.30	0.50	0.012	0.020
c	0.10	0.20	0.004	0.008
D	2.80	3.00	0.110	0.118
E	1.20	1.40	0.047	0.055
E1	2.25	2.55	0.089	0.100
e	0.950TYP		0.037TYP	
e1	1.80	2.00	0.071	0.079
L	0.550REF		0.022REF	
L1	0.30	0.50	0.012	0.020
θ	-	8°	-	8°

Suggested Pad Layout



Symbol	Dimensions			
	Millimeters		Inches	
	Min.	Max.	Min.	Max.
J	0.75	0.85	0.030	0.033
K	0.85	0.95	0.033	0.037
M	1.95	2.05	0.077	0.081
N	1.85	1.95	0.073	0.077